

## Cartridge relief valve with improved stability

**Patent number:** EP1312843  
**Publication date:** 2003-05-21  
**Inventor:** SLAWINSKI TOMASZ (US); CHEN JIANPING (US)  
**Applicant:** HYDRAFORCE INC (US)  
**Classification:**  
- **International:** **F16K17/10; F16K17/04;** (IPC1-7): F16K17/00  
- **European:** F16K17/10B  
**Application number:** EP20020090380 20021115  
**Priority number(s):** US20010333086P 20011116


**Cited documents:**

US3608576  
US4351356  
US5769113  
GB1009494  
JP56113867

Report a data error here


### Abstract of EP1312843

A cartridge relief valve (50) is uses a piston design. The piston (38) replaces a tube used in prior art relief valves. The piston (38) makes the inventive relief valve (50) easier to manufacture and more stable than prior art relief valves. This is due to the fact that, for a given size valve, the diameter of the piston (38) is smaller than the diameter of the tube that it replaces. Furthermore, the diameter of the pilot seat (66) of the inventive relief valve (50) is also smaller than the diameter of the pilot seat of many prior art valves.



Data supplied from the **esp@cenet** database - Worldwide

BEST AVAILABLE COPY



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 312 843 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
21.05.2003 Bulletin 2003/21

(51) Int Cl.7: **F16K 17/00**

(21) Application number: **02090380.3**

(22) Date of filing: **15.11.2002**

(84) Designated Contracting States:  
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR  
IE IT LI LU MC NL PT SE SK TR**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventors:  
• **Slawinski, Tomasz**  
Northbrook, IL 60065 (US)  
• **Chen, Jianping**  
Gurnee, IL 60031 (US)

(30) Priority: **16.11.2001 US 333086 P**

(74) Representative: **Pfenning, Meinig & Partner GbR**  
Joachimstaler Strasse 10-12  
10719 Berlin (DE)


(71) Applicant: **HydraForce, Inc.**  
Lincolnshire, Illinois 60069 (US)

(54) **Cartridge relief valve with improved stability**

(57) A cartridge relief valve (50) is uses a piston design. The piston (38) replaces a tube used in prior art relief valves. The piston (38) makes the inventive relief valve (50) easier to manufacture and more stable than prior art relief valves. This is due to the fact that, for a

given size valve, the diameter of the piston (38) is smaller than the diameter of the tube that it replaces. Furthermore, the diameter of the pilot seat (66) of the inventive relief valve (50) is also smaller than the diameter of the pilot seat of many prior art valves.

**FIG. 3**



**EP 1 312 843 A1**

## Description

### CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of the filing date of U.S. Provisional Application No. 60/333,086, filed on November 16, 2001.

### TECHNICAL FIELD

[0002] The invention relates generally to relief valves, and, more particularly, to cartridge relief valves that have a built-in reverse flow check valve structure.

### BACKGROUND

[0003] Relief valves are generally used to limit the maximum pressure in fluid systems. There are a variety of relief valves available on the market today. However, valve manufacturers are constantly seeking ways to improve the performance of such valves and to lower the amount of money and time it takes to manufacture them.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0004] While the appended claims set forth the features of the present invention with particularity, the invention may be best understood from the following detailed description taken in conjunction with the accompanying drawings of which:

[0005] FIG. 1 illustrates a prior art cartridge relief valve;

[0006] FIG. 2 illustrates a piston according to an embodiment of the invention;

[0007] FIGS. 3 - 7 illustrate a relief valve in accordance with an embodiment of the invention, with FIG. 5 further illustrating the relief valve in reverse flow mode;

[0008] FIG. 8 illustrates the flow characteristics of the prior art relief valve of FIG. 1; and

[0009] FIG. 9 illustrates the flow characteristics of an embodiment of the invention.

### DETAILED DESCRIPTION

[0010] The invention is generally directed to a cartridge relief valve having a piston design that makes the relief valve easier to manufacture and more stable than prior art relief valves.

[0011] Referring to FIG. 1, an example of a prior art relief valve will now be described. The relief valve 10 includes a generally cylindrical cage 12, a generally cylindrical adapter 14 and an adjuster 15. The cage 12 is coupled to one end of the adapter 14, while the adjuster 15 is coupled to the other end of the adapter 14. The relief valve 10 has a first port 11 and a second port 13, which are defined in the cage 12. The cage 12 has a sloped surface 12a near the second port 13, which is referred to herein as a seat 12a. Slideably disposed in-

side the cage 12 is a main poppet 16 having an axial bore 18. The main poppet 16 has a sloped face 16a. In the position depicted in FIG. 1, the poppet face 16a contacts the seat 12a of the cage 12 to form a metal seal that blocks communication between the first port 11 and the second port 13. A pilot seat 20 is disposed adjacent to the main poppet 16 and is fixed within the cage 12. The pilot seat 20 has an orifice 22. A first chamber 24 is defined between the pilot seat 20 and the main poppet 16. A tube 28 is slideably disposed within the axial bore 18 of the main poppet 16. In the position shown in FIG. 1, the tube 28 extends partially out of the main poppet 16 near the first port 11 at one end and partially into the chamber 24 at the other end.

The tube 28 has an axial bore 29 that communicates with the chamber 24 when the tube 28 is in the position shown in FIG. 1. Located within the first chamber 24 are a main spring 26 and a support spring 26a. The main spring 26 is in contact with the tube 28 at one end and with the pilot seat 20 at the other end. The support spring 26a is in contact with the tube 28 at one end and with the main poppet 16 at the other end. The main spring 26 and the support spring 26a keep the tube 28 in a free floating position with one end of the tube 28 facing away from the pilot seat 20.

[0012] Referring again to FIG. 1, the relief valve 10 further includes a second chamber 30 defined in the adapter 14 between the adjuster 15 and the pilot seat 20. A pilot poppet 31 is slideably disposed in the second chamber 30. The pilot poppet 31 has a ball seal 32. A pilot spring 34 is disposed in the second chamber 30, and is in contact with both the pilot poppet 31 and the adjuster 15. The spring 34 biases the pilot poppet 31 toward the orifice 22 of the pilot seat 20, so that, when the fluid pressure at the orifice is less than the force provided by the pilot spring 34, the ball seal 32 abuts the orifice 22. The adjuster 15 can be adjusted to move closer or farther away from the pilot poppet 31, thereby increasing or decreasing the biasing force of the pilot spring 34. The dimensions of the ball seal 32 are appropriate for preventing the flow of fluid through the orifice 22. A passageway 36 is defined between the inner surface of the adapter 14 and the outer surface of the cage 12, and provides communication between the second chamber 30 and the second port 13.

[0013] The relief valve 10 of FIG. 1 is designed to limit the pressure difference between the first port 11 and the second port 13, and to permit fluid to flow freely from the second port 13 to the first port 11. Under normal working conditions, fluid from the first port 11 flows through the axial bore 29 of the tube 28 and into the first chamber 24, until the pressure of the fluid in the first chamber 24 equals the pressure of the fluid at the first port 11. When the pressure of the fluid in the first chamber 24 exceeds the pressure value set by the biasing force of the pilot spring 34, the fluid pushes the pilot poppet 30 away from the orifice 22 of the pilot seat 20, exits the first chamber 24 and enters the second chamber 30. Fluid also flows

through the axial bore 29 of the tube 28 and into the second chamber 30. Finally, the fluid in the second chamber 30 travels through the passageway 36 and out of the second port 13. The flow of fluid out of the chamber 24 causes the pressure in the chamber 24 to drop, which causes the tube 29 to move against the main spring 26 and toward the orifice 22 of the pilot seat 20, until it moves through the orifice 22 of the pilot seat 20 and abuts the ball seal 32 of the pilot poppet 30, at which point the ball seal 32 restricts the flow of the fluid through the axial bore 29 of the tube 28. This action forms two flow restrictions - one between the tube 28 and the pilot poppet 31 and another between the tube 28 and the rim of the orifice 22. When the force created by pressure of the fluid in the first chamber 24 is lower than the force created by the pressure of the fluid at the first port 11, then the main poppet 16 moves away from the seat 12a of the cage 12, thereby opening a flow path between the first port 11 and the second port 13.

[0014] The relief valve 10 of FIG. 1 also has a reverse flow mode. In the reverse flow mode, when the fluid pressure at the second port 13 exceeds the fluid pressure at the first port 11, the pressure difference causes the main poppet 16 to move away from the first port 11. This action results from the geometry of the main poppet 16, and, in particular, the fact that a small, slanted portion 16a of the main poppet 16 is exposed to the second port 13. When the main poppet 16 moves away from the first port 11, fluid is permitted to flow directly from the second port 13 to the first port 11. Furthermore, the movement of the main poppet 16 away from the first port 11 compresses the fluid in the first chamber 24, thereby forcing the fluid from the first chamber 24, through the axial bore 29 of the tube 28, and out of the first port 11.

[0015] Referring to FIG. 2, a piston that functions according to an embodiment of the invention will now be described. The piston 38 has a first stem 40, a second stem 41 and a head 42 disposed between the first and second stems. The head 42 includes a step 49. The first stem 40 includes a slotted portion 44 having a pair of slots 46. Each of the pair of slots 46 has a leading edge 47. The first stem 40 also includes a non-slotted portion 48. In FIG. 2, only one of the pair of slots 46 is visible, but both slots 46 can be seen in FIGS. 3 - 7, in which a relief valve 50 that incorporates the piston 38 is shown. The relief valve 50 has many of the same components as the relief valve 10 of FIG. 1.

For example, the relief valve 50 includes a generally cylindrical cage 52, a generally cylindrical adapter 54 and an adjuster 56. The cage 52 is coupled to one end of the adapter 54, while the adjuster 56 is coupled to the other end of the adapter 54. The relief valve 50 has a first port 58 and a second port 60, which are defined in the cage 52. The cage 52 has a sloped surface 52a near the second port 60. Slideably disposed inside the cage 52 is a main poppet 62 having an axial bore 64. The main poppet 62 has a sloped face 62a. In the position depicted in FIGS. 3 and 4, the main poppet face 62a

contacts the seat 52a of the cage 52 to form a metal seal that blocks communication between the first port 58 and the second port 60. A pilot seat 66 is disposed adjacent to the main poppet 62 and is fixed within the cage 52. The pilot seat 66 has an orifice 68. A first chamber 70 is defined between the pilot seat 66 and the main poppet 62. Located within the first chamber 70 is a main spring 72. The piston 38 is slideably disposed within the axial bore 64 of the main poppet 62, with the head 42 of the piston 38 being disposed in the first chamber 70. In FIGS. 3 and 4, the piston 38 is shown in a first position, in which all of the non-slotted portion 48 of the first stem 40, and at least part of the slotted portion 44 extend partially out of the axial bore 64 of the main poppet 62 near the first port 58.

In FIG. 4, the piston 38 is shown in a second position, in which all of the slotted portion 44 of the first stem 40 is inside the axial bore 64 of the main poppet 62, and in which at least part of the non-slotted portion 48 is also inside the axial bore 64 of the main poppet 62. The main spring 72 is in contact with the head 42 and is disposed around the step 49 (from FIG. 2). The main spring 72 is also in contact with the pilot seat 66. The main spring 72 exerts a force to bias the piston 38 toward the first port 58. Should this biasing force be overcome, so as to cause the piston 38 to compress the main spring 72, the step 49 limits the motion of the piston 38 and prevents the main spring 72 from being overstressed.

[0016] Referring again to FIGS. 3 - 7, the relief valve 50 further includes a second chamber 74 defined in the adapter 54 between the adjuster 56 and the pilot seat 66. A pilot poppet 76 is slideably disposed in the second chamber 74. The pilot poppet 76 has a ball seal 78. A pilot spring 80 is disposed in the second chamber 74, and is in contact with both the pilot poppet 76 and the adjuster 56. The pilot spring 80 biases the pilot poppet 76 toward the orifice 68 of the pilot seat 66, so that, when the force created by the fluid pressure at the orifice is less than the force provided by the pilot spring 80, the ball seal 78 abuts the orifice 68. The adjuster 56 can be adjusted to move closer or farther away from the pilot poppet 76, thereby increasing or decreasing the biasing force of the pilot spring 80. The dimensions of the ball seal 78 are appropriate for preventing the flow of fluid through the orifice 68. A passageway 82 is defined between the inner surface of the adapter 54 and the outer surface of the cage 52, and provides communication between the second chamber 74 and the second port 60.

[0017] In accordance with an embodiment of the invention, an example of how the relief valve 50 of FIGS. 3 - 7 operates will now be described. In this example, it is assumed that the piston 38 is initially in the first position, as shown in FIGS. 3 and 4, in which the first port 58 is in fluidic communication with the first chamber 70 via the slots 46 of the piston 38. It is also assumed that the main poppet 62 is initially in the position depicted in FIGS. 3 and 4, in which it prevents any communication between the first port 58 and the second port 60. It is

further assumed that a pressure spike has occurred at the first port 58 and quickly propagates into the first chamber 70 through the slots 46. As a result, the pressure in the first chamber 70 increases sufficiently to force the pilot poppet 76 away from the orifice 68, thereby unblocking the orifice 68. Fluid then flows from the first chamber 70, through the orifice 68, through the second chamber 74, through the passageway 82 and out of the second port 60. This movement of fluid causes the pressure in the first chamber 70 to drop. The resulting differential pressure between the first port 58 and the first chamber 70 causes the piston 38 to move toward the orifice 68 until it moves into a position in which the leading edge 47 of the slot 46 enters the bore 64 of the poppet 62. This creates a first restriction on the pilot flow between the main poppet 62 and the stem 40 of the piston 38. The first restriction limits the flow of fluid from the first port 58 to the first chamber 70, thereby causing the pressure in the first chamber 70 to drop quickly and, as a result, causing the main poppet 62 to move toward the pilot seat 66. This opens a flow passage between the face 62a of the main poppet 62 and the seat 52a of the cage 52, thereby permitting fluid to flow from the first port 58 directly to the second port 60. Furthermore, the piston 38 moves toward the pilot seat 66, as shown in FIG. 6. This process repeats itself until the second stem 41 of the piston 38 enters the orifice 68. At that point, there a second clearance is created between the wall of the orifice 68 and the second stem 41. FIG. 6 shows the configuration of the valve at this point, and depicts the first restriction (reference numeral 84) and the second restriction (reference numeral 86). Ultimately, the piston 38 moves far enough into the orifice 68 as to make contact with the ball seal 78 and to keep the orifice 68 unblocked, as shown in FIG. 7.

[0018] At this point, the pilot flow (the flow of fluid from the first chamber 70 to the second chamber 74) is restricted, and is controlled by the movement of the main poppet 62. Furthermore, the main poppet 62 now follows the movements of the piston 38. The main poppet 62 now throttles the passage of fluid between the cage seat 52a and the face 62 of the main poppet. This allows the relief valve 50 to have a smooth response and consistent performance compared to the prior art relief valve 10 of FIG. 1. This can be seen by comparing FIG. 8, which illustrates the performance characteristics of a prior art valve such as the one illustrated in FIG. 1, with FIG. 9, which illustrates the performance characteristics of an embodiment of the invention.

[0019] Additionally, the relief valve shown in FIGS. 3 - 9 and described herein reduces the working stress on pilot spring or, alternatively, increases the maximum possible pressure setting compared to the prior art relief valve of FIG. 1. This is due to the fact that, for a given size valve, the diameter of the piston is smaller than the diameter of the tube that it replaces. The diameter of the pilot seat of the inventive relief valve is also smaller than the diameter of the pilot seat of the prior art valve of FIG.

1. This decrease in diameter results from the fact that the invention uses a solid piston as opposed to the hollow tube of the prior art valve. Thus, wall thickness limitations that were present with the hollow tube no longer apply with the invention.

[0020] It can thus be seen that a new and useful cartridge relief valve has been provided. In view of the many possible embodiments to which the principles of this invention may be applied, it should be recognized that the embodiments described herein with respect to the drawing figure is meant to be illustrative only and should not be taken as limiting the scope of invention. Therefore, the invention as described herein contemplates all such embodiments as may come within the scope of the following claims and equivalents thereof.

#### Claims

##### 1. A relief valve comprising:

a first moveable member having an inner wall that defines an axial bore;  
a substantially solid piston slideably disposed within the axial bore;  
a stationary member having an orifice;  
a second movable member having at least a first position in which it blocks the orifice and a second position in which it permits at least some fluid to pass through the orifice,

wherein, during operation of the relief valve, fluid enters the valve through a first port, travels between the first moveable member and the piston to exert pressure on the second moveable member at the orifice, thereby causing the second moveable member to move to the second position and permitting the fluid to exit the relief valve through a second port of the relief valve.

2. The relief valve of claim 1, wherein the first and second moveable members are disposed on opposite sides of the stationary member from one another.

3. The relief valve of claim 1, further comprising a means for biasing the piston toward the first port.

4. The relief valve of claim 3, wherein the biasing means is a spring.

5. The relief valve of claim 3, wherein the biasing means is a spring comprising a first end in contact with the piston and a second end in contact with the fixed member.

6. The relief valve of claim 1, wherein the first and second moveable members are disposed on opposite sides of the stationary member, the relief valve fur-

ther comprising:

a first biasing means for biasing the piston toward the first port;  
a second biasing means for biasing the second moveable member toward the orifice.

7. The relief valve of claim 6, wherein the first biasing means is a first spring and the second biasing means is a second spring.

8. The relief valve of claim 6, wherein the second biasing means is a spring comprising a first end and a second end, the first end being in contact with the second moveable member, the relief valve further comprising:

an adjusting piece disposed such that the second moveable member is between the fixed member and the adjusting piece, wherein the second end of the spring is in contact with the adjusting piece, and wherein the adjusting piece can be adjusted to change the distance between itself and the second moveable member, thereby changing the compression of the spring.

9. The relief valve of claim 1, wherein the second moveable member is biased to remain in the first position by a force, the relief valve further comprising:

a means for adjusting the amount of the force.

10. A relief valve comprising:

an adapter having at least a first chamber and a second chamber;  
a moveable member disposed within the first chamber, the moveable member having an axial bore that communicates with the first chamber;  
a substantially solid piston partially disposed in the axial bore and partially disposed in the first chamber;  
a means for blocking communication between the first chamber and the second chamber,

wherein during operation of the relief valve, fluid travels between the piston and the axial bore, through the first chamber and exerts pressure on the blocking means, thereby causing the blocking means to move and to permit the fluid to enter the second chamber.

11. The relief valve of claim 10, wherein, when the fluid exits the first chamber through the orifice, the pressure in the first chamber drops, thereby causing the

piston to move toward the orifice.

12. The relief valve of claim 10, further comprising:

a first port; and  
a second port, wherein fluid enters the relief valve through the first port, travels between the piston and the axial bore, through the first chamber and exerts pressure on the blocking means, thereby causing the blocking means to move and to permit the fluid to enter the second chamber, and travels from the second chamber to the second port.

13. The relief valve of claim 10, further comprising:

a first port; and  
a second port, wherein the first moveable member blocks the flow of fluid between the first and second ports, and wherein fluid enters the relief valve through the first port, travels between the piston and the axial bore, through the first chamber and exerts pressure on the blocking means, thereby causing the blocking means to move and to permit the fluid to enter the second chamber, and travels from the second chamber to the second port, reducing the pressure in the first chamber and causing:

the piston to move toward the orifice, and the first moveable member to move toward the orifice, thereby permitting at least some fluid to flow from the first port to the second port without passing through the axial bore of the first moveable member.

14. A relief valve comprising:

a cage having an axial bore;  
a moveable member disposed within the axial bore of the cage, the moveable member comprising a first end and a second end, the moveable member having an axial bore extending from the first end to the second end;  
a fixed member disposed within the axial bore of the cage adjacent to the second end of the moveable member, a chamber being defined between the moveable member and the fixed member;  
a piston disposed within the axial bore of the moveable member and at least partially extending into the chamber, the piston comprising a stem having a slotted section and a non-slotted section, the piston having at least a first position, in which the non-slotted section is outside of the axial bore of the movable member at its first end, and a second position, in which the

non-slotted section is at least partially inside the axial bore,

wherein, when the piston is in the first position, the relief valve is capable of passing fluid through the axial bore of the movable member, around the slotted section of the piston, and through the chamber,

and wherein, in response to a decrease in pressure in the chamber, the piston moves toward the fixed member from the first position to the second position, thereby restricting the flow of the fluid through the axial bore.

15. The relief valve of claim 14, wherein the axial bore of the first moveable member is defined by a wall, wherein a slot is defined in the slotted portion of the stem, wherein the slot and the wall define a channel through which the fluid passes, and wherein when the piston is in the second position, the non-slotted portion and the wall define a clearance that restricts the flow of the fluid into the channel.

16. A relief valve comprising:

a cage having an axial bore and a first chamber; an adapter coupled to the cage and having a second chamber;

a first moveable member disposed within the axial bore of the cage, the first moveable member comprising a first end and a second end, the first moveable member having an axial bore extending from the first end to the second end; a fixed member disposed within the axial bore of the cage adjacent to the second end of the first moveable member, the first chamber being defined between the first moveable member and the fixed member, the fixed member having an orifice that connects the first chamber and the second chamber;

a second movable member disposed within the second chamber and on the opposite side of the fixed member as the first movable member, the second movable member being biased to obstruct the orifice;

a piston disposed within the axial bore of the moveable member and at least partially extending into the chamber, the piston comprising:

a first portion having a first diameter, a second portion having a second diameter, a third portion having a third diameter, wherein the second diameter is larger than both the first and the third diameters,

wherein the first portion is at least partially disposed in the axial bore of the first movable member and the second and third portions are at least partially disposed within the first chamber.

17. The relief valve of claim 16, further comprising a spring disposed in the first chamber and in contact with the fixed member at one end, and in contact with the piston at the other end.

18. The relief valve of claim 17, wherein the second portion of the piston has a step that limits the degree to which the spring can be compressed by the piston.

19. The relief valve of claim 16, wherein the third portion is aligned with the orifice so that, when the piston moves toward the fixed member, the third portion gets inserted into the orifice.

20. The relief valve of claim 16, further comprising:

an adjuster coupled to the adapter; and a spring disposed in the second chamber with one end of the spring being in contact with the fixed member and the other end of being in contact with the adjuster.

21. A valve having at least a first port and a second port, the valve comprising:


a moveable member having an axial bore, the moveable member having at least a first position in which it blocks a flow of fluid between the first and second ports and a second position in which it permits the flow of fluid between the first and second ports, wherein the moveable member moves in response to a change in pressure in the valve; and

a piston slideably disposed within the axial bore, wherein the relative movement between the piston and the moveable member alternately restricts and permits the flow of fluid through the axial bore, thereby regulating the pressure inside the valve and, as a result, regulating the movement of the moveable member.


22. The valve of claim 21, wherein the moveable member comprises a sloped face, the valve further comprising a cage having an axial bore, the cage comprising a seat disposed annularly within the axial bore near the second port,

wherein when the moveable member is in its first position, the movable member is disposed within the cage such that the sloped face contacts the seat to create a seal that prevents fluid from flowing directly between the first and second ports.

FIG. 1







3  
G.  
F.




FIG. 4





FIG. 5






FIG. 7




FIG. 8





FIG. 9

PRESSURE VS. FLOW







European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 02 09 0380

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.CI.7)
X	US 3 608 576 A (WILHELM RAYMOND L) 28 September 1971 (1971-09-28)  * column 2, line 25 - column 4, line 4 * * figures *	1,2, 9-13,16, 19-22	F16K17/00
A		3-8,14, 15,17,18	
X	US 4 351 356 A (KOIWA HIDEHI ET AL) 28 September 1982 (1982-09-28)  * column 5, line 52 - column 6, line 36 * * figure 3 *	1,2, 9-13,16, 20-22	
A		3-8,14, 15,17-19	
A	US 5 769 113 A (MCNEELY MICHAEL D ET AL) 23 June 1998 (1998-06-23)  * column 9, line 55 - column 11, line 24 * * figure 4 *	1,2, 9-16, 19-22	
A	GB 1 009 494 A (HYDRAULIC UNIT SPECIALITIES CO) 10 November 1965 (1965-11-10) * page 2, line 56 - page 4, line 68 * * figures 1,2 *	1-22	TECHNICAL FIELDS SEARCHED (Int.CI.7) F16K
A	PATENT ABSTRACTS OF JAPAN vol. 005, no. 193 (M-101), 9 December 1981 (1981-12-09) & JP 56 113867 A (KAYABA IND CO LTD), 8 September 1981 (1981-09-08) * abstract *	1,10,14, 16,21	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 18 February 2003	Examiner Ceuca, A-N
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03/92 (Practi)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 09 0380

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-02-2003

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 3608576	A	28-09-1971	NONE		
US 4351356	A	28-09-1982	JP	56020877 A	26-02-1981
US 5769113	A	23-06-1998	US	5590684 A	07-01-1997
			AU	6847396 A	27-03-1997
			CA	2230480 A1	13-03-1997
			EP	0842376 A1	20-05-1998
			NO	980787 A	28-04-1998
			WO	9709553 A1	13-03-1997
GB 1009494	A	10-11-1965	NONE		
JP 56113867	A	08-09-1981	NONE		

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**